



ALLOY 6060 : 5 METRE LENGTHS

SECTION	EX STOCK	SIZE mm			RADII mm	KILO / METRE	PERIMETER mm
		A	B	T	R (E / I)		
60048	✓	12.00	12.00	1.50	0.30 (E)	0.091	47.4
60041	*	12.00	12.00	1.60	0.30 (E)	0.097	47.4
	*	12.00	12.00	3.00		0.170	48.0
90025	✓	16.00	16.00	1.60		0.132	64.0
30233	*	19.00	19.00	1.50		0.148	76.0
60091	*	20.00	20.00	1.40	0.20 (E)	0.146	79.6
10160	✓	20.00	20.00	1.60		0.166	80.0
30892	✓	20.00	20.00	3.00	0.20 (E)	0.301	79.6
60008	*	25.00	25.00	1.40	0.30 (E)	0.184	99.4
10159	✓	25.00	25.00	1.60		0.210	100.0
30079	✓	25.00	25.00	3.00		0.382	99.5
	*	25.00	25.00	5.00		0.610	100.0
30884	*	30.00	30.00	2.00	0.30 (E)	0.314	119.4
30249	✓	30.00	30.00	3.00		0.463	120.0
90194	*	30.00	30.00	5.00		0.745	120.0
	*	30.00	30.00	6.00	0.40 (E)	0.878	120.0
60005	*	32.00	32.00	1.60	0.30 (E)	0.270	127.4
60006	✓	32.00	32.00	3.00	0.30 (E)	0.496	127.4
60045	*	40.00	40.00	1.40	0.30 (E)	0.298	159.4
30893	✓	40.00	40.00	1.60	0.20 (E)	0.304	159.6
60079	*	40.00	40.00	2.00	0.50 (E)	0.422	158.9
30080	✓	40.00	40.00	3.00		0.626	159.5
30415	✓	40.00	40.00	4.50	0.50 (E)	0.921	159.6
60144	✓	40.00	40.00	6.00	0.20 (E)	1.203	159.6
60067	✓	50.00	50.00	1.60	0.30 (E)	0.426	199.4
30232	✓#	50.00	50.00	3.00		0.789	200.0
30082	✓#	50.00	50.00	4.50	1.00 (I)	1.165	199.0
30081	✓	50.00	50.00	6.00		1.528	199.5
90236	✓	60.00	60.00	3.00		0.948	240.0
	*	60.00	60.00	6.00		1.847	240.0
30629	✓	65.00	65.00	6.00	0.20 (E)	2.016	259.6
60218	✓	75.00	75.00	3.00	0.30 (E)	1.195	299.6
30742	✓	75.00	75.00	4.50	0.30 (E)	1.774	299.4
30336	✓	75.00	75.00	6.00		2.341	300.0
	*	76.20	76.20	3.00		1.210	304.0
	*	76.20	76.20	9.00		3.485	304.8
60168	*	100.00	100.00	3.00	0.30 (E)	1.601	399.4
60153	✓	100.00	100.00	6.00	0.30 (E)	3.154	399.4
20001	✓	100.00	100.00	10.00	5.00 (E)	5.134	397.9

A = Width B = Height T = Thickness I = Internal Radii R = External Radii

* Mill runs only, please ask regarding the availability of these # Other stock lengths available in this size.