



ALLOY 5005

EX STOCK	THICKNESS mm	WIDTH mm	LENGTH mm	ALLOY TYPE	TEMPER	KILO / SHEET
	T	W	L			
*	0.45	900	2450	3003	H12	2.65
*	0.55	900	2400	3003	H12	3.24
*	0.55	1200	2400	3003	H12	4.27
*	0.55	1200	2400	5005	H32	4.27
*	0.7	900	2400	5005	H32	4.08
✓	0.7	1200	2400	5005	H34	5.44
✓	0.7	1200	3000	5005	H34	6.80
✓	0.9	900	2400	5005	H34	5.24
✓	0.9	1200	2400	5005	H34	7.00
✓	0.9	1200	3600	5005	H34	10.49
✓	1.2	1200	2400	5005	H34	9.33
✓	1.2	1200	3600	5005	H34	13.99
✓	1.2	1200	5000	5005	H34	19.44
✓	1.2	1200	6000	5005	H34	23.41
✓	1.2	1500	3000	5005	H34	14.58
✓	1.5	1200	2400	5005	H32	11.66
✓	1.5	1200	3600	5005	H32	17.49
✓	1.5	1200	5000	5005	H32	24.30
✓	1.5	1200	6000	5005	H32	29.26
✓	1.5	1500	3000	5005	H32	18.22
✓	1.5	1500	3600	5005	H32	21.87
✓	2.0	1200	2400	5005	H32	15.55
✓	2.0	1200	3000	5005	H32	19.44
✓	2.0	1200	3600	5005	H32	23.33
✓	2.0	1200	5000	5005	H32	32.40
✓	2.0	1200	6000	5005	H32	38.90
✓	2.0	1500	3000	5005	H32	24.30
✓	2.0	1500	3600	5005	H32	29.16
✓	2.5	1200	2400	5005	H32	19.44
*	2.5	1500	3000	5005	H32	30.37
✓	3.0	1200	2400	5005	H32	23.33
✓	3.0	1200	3000	5005	H32	29.16
✓	3.0	1200	3600	5005	H32	34.99
✓	3.0	1500	3000	5005	H32	36.45
✓	3.0	1500	3600	5005	H32	43.74
5005 ANODISED SHEET SATIN, 25 MICRON						
✓	1.20	1200	2400	5005	H34	9.33

T = Thickness W = Width L = Length

* Please ask regarding the ex stock availability. All sheet is mill finish unless otherwise stated